



1 US gal. • 5 US gal.

SRW PAVER SEAL PLUS

SRW Paver Seal Plus is a clear, low-gloss penetrating sealer. Perfect for repelling water and dirt, and protecting against salt and frost damage on retaining walls and patios. It enhances and retains the original appearance of pavers, brick, block, stone, masonry, and concrete surfaces with a UV resistant finish. Upon penetration, Paver Seal Plus inhibits water absorption which causes efflorescence, spalling and freeze/thaw damage. Its special formula makes it ideal for both horizontal and vertical applications. Minimizes cleaning and maintenance, while extending the life of your pavers against elements which can deteriorate your pavement's appearance, such as rust, oil, dirt, pool chemicals and salt. Easy installation.

- Interior/Exterior
- Seals and protects
- Environmentally friendly
- Horizontal and vertical applications
- Clear, low-gloss, natural finish
- VOC Compliant

DIRECTIONS

1. For best results, surface must be clean (remove stains, efflorescence, dirt and loose materials) and thoroughly dry prior to sealer application. We recommend preparation of the surface with SRW Efflorescence Cleaner for removal of efflorescence and SRW Cleaner/Degreaser for removal of stains. Do not apply at a temperature below 50°F (10°C) or above 80°F (27°C).
2. Apply Paver Seal Plus thoroughly and evenly with a roller, squeegee or airless sprayer. On vertical applications, apply from the bottom up achieving a 6-8 inch rundown. Uneven application may lead to uneven appearance.
3. Allow pavement to dry and cure 24 hours before subjected to normal traffic. Very porous surfaces may require two applications. Wait 4 hours between applications.

Cleanup • Clean with soap and warm water.

USER TIPS

- Surface may be damp or wet, however the dryer the surface, the better the absorption.
- When using on aged surfaces, make sure that surface is clean and that any damaged areas have been repaired.
- For new pavement, let efflorescence (white mineral deposits) rise to the surface for at least 90 days before cleaning and sealing.
- Do not apply to structures under hydrostatic pressure.
- Lower temperatures or high humidity will increase drying time.
- For extra joint protection use SRW Joint Set™ Sand Stabilizer before sealing.
- Apply yearly to retaining walls under harsh freeze/thaw (salt) conditions.

Coverage: 100-125 sq. ft. per gallon, depending on surface porosity and application.

PACKAGING

PART NUMBER	SIZE	# PER CARTON OR PALLET	LBS
SSPSPLUS GAL / SSPSPLUS CTN	1 US Gallon	4/carton; 45 cartons/pallet	37/carton 1665/pallet
SSPSPLUS 5GAL	5 US Gallon	36/pallet	47/pail 1692/pallet

WARNINGS

KEEP PRODUCT FROM FREEZING.

KEEP OUT OF REACH OF CHILDREN.

Caution: Protect buildings, landscaping and vehicles from overspray or spray drift.

Storage: Keep from freezing. Store container in a cool area, away from heat and open flame, with cap or lid firmly in place.

Warning: Do not inhale spray mist. Irritating to skin and eyes. In case of eye contact, flush with water for at least 15 minutes. Wash exposed skin with warm, soapy water. If irritation persists, see a physician. If ingested, do NOT induce vomiting. Dilute by drinking water. Seek medical attention. Always wear a mask and protective eyewear and clothing. **Keep out of reach of children.**

Important Notice:

Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.