



1 US gal. • 5 US gal.

SRW PAVER SEAL

SRW Paver Seal™ is a protective barrier that minimizes the absorption of water and stains into paver, brick, block, stone, masonry and concrete surfaces. It produces a clear, low-gloss, natural finish that can be used on interior and exterior surfaces. At the same time, Paver Seals' active ingredients seal the sand joints from washout, weed growth and ant invasion. Paver Seal preserves the natural beauty of your pavement, while adding UV resistants against fading or yellowing. It extends the life of your pavers against elements which can deteriorate your pavement's appearance, such as rust, oil, dirt, pool chemicals and salt. Easy installation and low maintenance.

- Interior/Exterior
- UV Resistant
- Environmentally friendly
- Seals, bonds and protects
- Clear, low-gloss, natural finish
- VOC Compliant

DIRECTIONS

1. Surface must be clean (remove stains, efflorescence, dirt and loose materials) prior to application. We recommend preparation of the surface with SRW Efflorescence Cleaner for removal of efflorescence and SRW Cleaner/Degreaser for removal of stains.
2. Surface must be completely dry prior to sealer application. Do not apply at a temperature below 50°F (10°C) or above 80°F (27°C).
3. Apply Paver Seal evenly with a sprayer, roller, or squeegee. Direct excess sealer off the surface or into the joints to bond the joint sand. Uneven application may lead to uneven appearance.
4. Allow to dry for approximately 4 hours before applying a lighter, second coat. Following second coat, allow pavement to dry and cure 24 hours before subjected to normal traffic.

Cleanup • Clean with soap and warm water.

USER TIPS

- For new pavement, let efflorescence (white mineral deposits) rise to the surface for at least 90 days before cleaning and sealing.
- Apply two thin coats for best results. Do not over apply.
- Do not use if inclement weather is forecasted within 24 hours.
- Lower temperatures or high humidity will increase drying time.
- For extra joint protection use SRW Joint Set™ Sand Stabilizer before sealing.

Coverage: 100-175 sq. ft. per gallon exterior pavement coverage (based on an 1/8" joint spacing). Quantity may vary depending on surface and application.

PACKAGING

PART NUMBER	SIZE	# PER CARTON OR PALLET	LBS
SSPS GAL / SSPS CTN	1 US Gallon	4/carton; 45 cartons/pallet	37/carton 1665/pallet
SSPS 5GAL	5 US Gallon	36/pallet	47/pail 1692/pallet

WARNINGS

KEEP PRODUCT FROM FREEZING.

KEEP OUT OF REACH OF CHILDREN.

Caution: Protect buildings, landscaping and vehicles from overspray or spray drift.

Storage: Keep from freezing. Store container in a cool area with cap or lid firmly in place.

Warning: Do not inhale spray mist. Irritating to skin and eyes. In case of eye contact, flush with water for at least 15 minutes. Wash exposed skin with warm, soapy water. If irritation persists, see a physician. If ingested, do NOT induce vomiting. Dilute by drinking water. Seek medical attention. Always wear a mask and protective eyewear and clothing. **Keep out of reach of children.**

Important Notice:

Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.