



PAVER SEAL PRO



1 US gal. • 5 US gal. • 55 US gal

SRW PAVER SEAL™ PRO

SRW Paver Seal Pro is a high solids, acrylic waterbase sealer offering high-gloss, greater long term protection and easy application. It quickly forms a hard clear protective film that is tough, slip resistant, dustproof, and non-yellowing. This product is ideal for interior and exterior applications on new and existing floors, pavers, stamped and decorated concrete surfaces. Provides protection from deicing salts, staining and harmful environmental elements.

- Interior/Exterior
- UV Resistant
- Breathable
- Slip resistant
- Seals, bonds and protects
- Clear, high-gloss finish
- VOC Compliant
- Easy application

GENERAL DIRECTIONS

- 1) Thoroughly mix before applying. Product is supplied at the proper consistency for application and dilution will reduce efficiency and gloss.
- 2) Apply by low-pressure high solids commercial grade solvent resistant sprayer (an adjustable fan tip allows for best control). The sprayer must be clean and dry. If sprayer is not available, use a brush or 1/4" roller. If applying by roller, do not over-work material. Do not back roll or allow the working area to dry.
- 3) Material should not be allowed to puddle. Broom out or squeegee excess.
- 4) Do not seal if inclement weather is forecasted within 24-hours.
DRY TIMES: Tack free: 25 minutes; Foot traffic: 24 hours; Vehicle traffic: 72 hours (Calculations are based upon temperatures 68-77° F [20-25° C]. Lower temperatures and/or high humidity will extend dry times.)
- 5) Protect all areas from over spray.
- 6) The sealer can be applied to damp surfaces, however, do not apply over puddled water. (See "Sealing Pavers" section below for joint sand stabilization.)
- 7) A uniform appearance requires even coats leaving no gaps. Some areas may be more porous than others; these areas may require additional coats to even out the appearance. Caution: Do not over-apply material.

SEALING PAVERS

- 1) Thoroughly clean surface prior to application. Remove dirt and stains using *SRW Cleaner & Degreaser*. Remove efflorescence using *SRW Efflorescence Cleaner*. Joints must be full of sand and **completely** dry prior to application. Brush off all joint sand, dust and loose material. Apply first coat evenly in a lapping motion at 100-200 sq.ft./gal. Coverage will depend on the texture of the pavers and width of joint. Perform a test area to determine proper application technique and rate. Ensure joints receive an adequate amount of sealer. Excess material around joints should be spread evenly over pavers with a squeegee. A second coat is recommended for long term durability and gloss.

Second Coat: A second coat may be applied approximately 4-hours after the first coat (depending on weather). Apply second coat as directed at 400-500 sq.ft. /gal (10-12.5 m IL).

PACKAGING

PART NUMBER	SIZE	# PER CARTON OR PALLET	LBS
SSSPRO GAL / SSSPRO CTN	1 US Gallon	4/carton; 45 cartons/pallet	34/carton 1530/pallet
SSSPRO 5GAL	5 US Gallon	36/pallet	44/pail 1584/pallet
SSSPRO 55GAL	55 US Gallon	NA	485

WARNINGS

KEEP PRODUCT FROM FREEZING.

KEEP OUT OF REACH OF CHILDREN.

PHYSICAL PROPERTIES

Wet appearance: Milky White
 Dry appearance: Clear
 Solids: 30% minimum

HEALTH AND SAFETY

- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Use of appropriate NIOSH respirator is advised when using in confined areas.

Caution: Protect buildings, landscaping and vehicles from overspray or spray drift.

Storage: Keep from freezing. Store container in a cool area, away from heat and open flame, with cap or lid firmly in place.

Warning: Do not inhale spray mist. Irritating to skin and eyes. In case of eye contact, flush with water for at least 15 minutes. Wash exposed skin with warm, soapy water. If irritation persists, see a physician. If ingested, do NOT induce vomiting. Dilute by drinking water. Seek medical attention. Always wear a mask and protective eyewear and clothing. **Keep out of reach of children.**

Important Notice:

Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.